

Figure 1 Conventional Noise Feedback Coding



Figure 1A Noise Feedback Coding Using Composite Short-Term and Long-Term Predictors and Composite Short-Term and Long-Term Filter

Replacement Sheet
Sheet 2 of 36
Appl. No. 10/084,503; Filed: Feb 28, 2002
Dkt No. 1875.1760001; Group Unit: 2626
Inventors: THYSSEN et al.
Tel. No.: 202-371-2600
For: Efficient Excitation Quantization in a Noise Feedback Coding System Using Correlation Techniques



Figure 2 An alternative form of conventional Noise Feedback Coding



Figure 2A Noise Feedback Coding Using Composite Predictor and Composite Noise Filter



Figure 3 Noise Feedback Coding with short-term and long-term prediction but only short-term noise spectral shaping

Replacement Sheet
Sheet 5 of 36
Appl. No. 10/084,503; Filed: Feb 28, 2002
Dkt No. 1875.1760001; Group Unit: 2626
Inventors: THYSSEN et al.
Tel. No.: 202-371-2600
For: Efficient Excitation Quantization in a Noise Feedback Coding System Using Correlation Techniques



Figure 4 Nested two-stage Noise Feedback Coding structure with short-term and long-term prediction and short-term and long-term noise spectral shaping



Figure 5 An alternative nested two-stage Noise Feedback Coding structure with short-term and long-term prediction and short-term and long-term noise spectral shaping



FIG. 5A



Figure 6 Another alternative nested two-stage Noise Feedback Coding structure with short-term and long-term prediction and short-term and long-term noise spectral shaping


START
6050
Predict a speech (or audio) signal (e.g., s(n)) to produce a predicted speech signal (e.g., ps(n))
6055
Combine the predicted speech signal (e.g., ps(n)) with the speech signal (e.g., s(n)) to produce a first residual signal (e.g., d(n))
6060
Combine the first residual signal (e.g., d(n)) with a first noise feedback signal (e.g., fqs(n)) to produce a predictive quantizer input signal (e.g., v(n))
6062
Predictively quantize the predictive quantizer input signal (e.g., v(n)) to produce a predictive quantizer output signal (e.g., vq(n)) associated with a predictive quantization noise (e.g., qs(n))
6064
Filter the predictive quantization (e.g., qs(n)) to produce the first noise feedback signal (e.g., fqs(n))
6066
END

FIG. 6A


6064
START
Predict the predictive quantizer input signal (e.g., v(n)) to produce a first predicted predictive quantizer input signal (e.g., pv(n))
6070
In all embodiments: Combine the predictive quantizer input signal (e.g., (vn)) with at least the first predicted predictive quantizer input signal (e.g., pv(n)) to produce a quantizer input signal (e.g., u(n)).
In the embodiments including an inner noise feedback loop: Further combine a second noise feedback signal (e.g., fq(n)) with the predictive quantizer input signal (e.g., v(n)) and the first predicted predictive quantizer input signal (e.g., pv(n)), to produce the quantizer input signal (e.g., u(n)).
6072
Quantize the quantizer input signal (e.g., u(n)) to produce a quantizer output signal (e.g., uq(n))
6076
In embodiments including the inner noise feedback loop: Filter a quantization noise (e.g., (q(n)) associated with the quantizer output signal (e.g., q(n)) to produce the second noise feedback signal (fq(n))
6078
Derive the predictive quantizer output signal (e.g., vq(n)) based on the quantizer output signal (e.g., uq(n))
6080
END

FIG. 6B



Figure 7 Encoder of a nested two-stage noise feedback codec (TSNFC)



Figure 8 Decoder corresponding to the TSNFC encoder in Fig. 7



Figure 9 Short-term predictive analysis and quantization (block 10)



Figure 10 LSP quantizer (block 16)



Figure 11 Long-term predictive analysis and quantization (block 20)



Figure 12 Prediction residual quantizer (block 30)


1300
1312
Preferred Code Vector Selector
e(n)
1310
Error Energy Calculator
5028a
1302
VQ Codebook
g(n)
1304
q(n)
1308
Input Vector Deriver
(u(n) → uq(n))
1314
Predictor/Filter Restorer
d(n)
Controller
1306
Predictor Logic
s(n)

FIG. 13A


1350
START
Predict a speech signal s(n) to derive a residual signal d(n)
1352
Derive N VQ input vectors u(n) each corresponding to one of N VQ error vectors, based on the residual signal d(n) and a corresponding one of N VQ codevectors
1354
Derive N VQ error energy values each corresponding to one of the N VQ error vectors q(n)
1358
Select a preferred one of the N VQ codevectors as a VQ output vector uq(n) corresponding to the residual signal d(n), based on the N VQ error energy values
1360
END

FIG. 13B



The portion of the codec structure that is used in prediction residual VQ codebook search of the two-stage noise feedback codec of Fig. 5.

FIG. 13C


1364
START
Combine each of the N VQ input vectors u(n) (from step 1354 in Fig. 13B) with the corresponding one of the N VQ code vectors (also from step 1354) to produce the N VQ error vectors q(n)
1365
Filter at least a portion of each of the N VQ error vectors q(n) to produce N noise feedback vectors fq(n), each corresponding to one of the N VQ codevectors
1366
Separately combine each of the N noise feedback vectors fq(n) with the residual signal d(n) to produce the N VQ input vectors u(n)
1368
START

FIG. 13D


1370
START
Separately combine the residual signal d(n) (from step 1352 of FIG. 13B) with each of the N noise feedback vectors fqs(n) to produce N predictive quantizer input vectors v(n)
1372
Predict each of the N predictive quantizer input vectors v(n) to produce N predicted, predictive quantizer input vectors pv(n)
1374
Combine each of the N predictive quantizer input vectors v(n) with a corresponding one of the N predicted, predictive quantizer input vectors pv(n), to produce the N VQ input vectors u(n)
1376
Combine each of the N predicted, predictive quantizer input vectors pv(n) with corresponding ones of the N VQ codevectors, to produce N predictive quantizer output vectors vq(n) corresponding to N VQ error vectors qs(n)
1378
Separately filter each of the N VQ error vectors qs(n) to produce the N noise feedback vectors fqs(n)
1380
END

FIG. 13E


1400
1412
Preferred Codevector Selector
5028a
1302
VQ Codebook
g(n)
1304
1410
Error Energy Calculator
qzi(n)
qzs(n)
1402
ZERO-INPUT Response Filter Structure
Restorer
1404
ZERO-STATE Response Filter Structure
1414
d(n)
1306
Predictor Logic
s(n)

FIG. 14A


1430
START
Predict a speech signal s(n) to derive a residual signal d(n)
1432
Derive a ZERO-INPUT response error vector qzi(n) common to each of N VQ codevectors
1434
Derive N ZERO-STATE response error vectors qzs(n) each based on a corresponding one of the N VQ codevectors
1436
Select a preferred one of the N VQ codevectors as a VQ output vector uq(n) corresponding to the residual signal d(n) based on the ZERO-INPUT response error vector qzi(n) and the N ZERO-STATE response error vectors qzs(n)
1438
END

FIG. 14B



Filter structure during the calculation of the zero-input response of q(n) of Fig. 13C.

FIG. 14C

Replacement Sheet
Sheet 25 of 36
Appl. No. 10/084,503; Filed: Feb 28, 2002
Dkt No. 1875.1760001; Group Unit: 2626
Inventors: THYSSEN et al.
Tel. No.: 202-371-2600
For: Efficient Excitation Quantization in a Noise Feedback Coding System Using Correlation Techniques


1450
START
Derive an intermediate vector vzi(n) based on the residual signal d(n)
1452
Predict the intermediate vector vzi(n) to produce a predicted intermediate vector vqzi(n)
1454
Combine the intermediate vector vzi(n) with the predicted intermediate vector vqzi(n) and a noise feedback vector fqzi(n) to produce the ZERO-INPUT response error vector qzi(n)
1456
Filter the ZERO-INPUT response error vector qzi(n) to produce the noise feedback vector fqzi(n)
1458
END

FIG. 14D


1470
START
Combine a residual signal d(n) with a noise feedback signal fqszi(n) to produce an intermediate vector vzi(n)
1472
Predict the intermediate vector vzi(n) to produce a predicted intermediate vector vqzi(n)
1474
Combine the intermediate vector vzi(n) with the predicted intermediate vector vqzi(n) to produce an error vector qszi(n)
1476
Filter the error vector qszi(n) to produce the noise feedback vector fqszi(n)
1478
END

FIG. 14E



Filter structure during the calculation of the zero-state response of q(n) in Fig. 13C.

FIG. 15A

Replacement Sheet
Sheet 28 of 36
Appl. No. 10/084,503; Filed: Feb 28, 2002
Dkt No. 1875.1760001; Group Unit: 2626
Inventors: THYSSEN et al.
Tel. No.: 202-371-2600
For: Efficient Excitation Quantization in a Noise Feedback Coding System Using Correlation Techniques


1520
START
Filter an error vector qszs(n) associated with each of the N VQ codevectors to produce a ZERO-STATE input vector vzs(n) corresponding to each of the N VQ codevectors
1522
Separately combine each ZERO-STATE input vector vzs(n) produced by the filter with the corresponding one of the N VQ codevectors, to produce the N ZERO-STATE response error vectors qzs(n)
1524
START

FIG. 15B



A filter structure equivalent to the structure in Fig. 15A.

FIG. 16A


1620
START
Combine each of the N VQ codevectors with a corresponding one of N filtered, ZERO-STATE response error vectors vzs(n) to produce the N ZERO-STATE response error vectors qzs(n)
1622
Separately filter each of the N ZERO-STATE response error vectors qzs(n) to produce the N filtered, ZERO-STATE response error vectors vzs(n)
1624
START

FIG. 16B


1700
START
Receive a speech signal comprising a sequence of speech vectors, each of the speech vectors including a plurality of speech samples
1702
Derive a gain value based on the speech signal once every M speech vectors, where M is greater than one
1704
Derive/update filter parameters based on the speech signal once every T speech vectors
1706
Derive the N ZERO-STATE response error vectors qzs(n) only once every T and/or M speech vectors (i.e., when the filter parameters and/or gain values are updated), whereby a same set of N ZERO-STATE response error vectors qzs(n) is used in selecting T and/or M preferred codevectors corresponding to the T and/or M speech vectors.
1708
END

FIG. 17


1800
Begin
Calculate zero-state responses of codebook vectors
1805
Calculate energies of zero-state response
1810
First vector
1815
Calculate zero-input response
1820
Next vector
1840
No
Last vector?
1835
Yes
Done
Select best codevector based on minimization term given by energy of zero-state response and cross-correlation between zero-input response and zero-state response
1825
Update filter memories based on selected best codevector
1830

FIG. 18


1900
Begin
1905
First codevector
1910
Retrieve pre-calculated zero-state response of codevector
1915
Calculate cross-correlation between zero-state response of codevector and zero-input response
1920
Retrieve pre-calculated energy of zero-state response of codevector
1925
Calculate minimum term of codevector as energy of zero-state response of codevector combined with cross-correlation between zero-state response of codevector and zero-input response
1930
Minimization term smaller than best?
Yes
1935
Update best
No
1940
Last vector?
Yes
Done
No
1945
Next vector

FIG. 19


Begin
2000
2005
First codevector in shape codebook
2010
Retrieve zero-state response of shape codevector
2055
Next codevector in shape codebook
No
2050
Last codevector in shape codebook?
Yes
Done
2015
Retrieve energy of zero-state response of shape codevector
2045
Update best
Yes
No
2020
Calculate cross-correlation term between zero-state response of shape codevector and zero-input response
2040
Minimization term smaller than best?
2030
2025
Positive cross-correlation term?
Yes
1. Sign is negative.
2. Calculate minimization term as energy of zero-state response minus cross-correlation term.
2035
No
1. Sign is positive.
2. Calculate minimization term as energy of zero-state response minus cross-correlation term.

FIG. 20


Computer System 2100
Processor 2104
Main Memory 2108
Secondary Memory 2110
Hard Disk Drive 2112
Removable Storage Drive 2114
Removable Storage Unit 2118
Interface 2120
Removable Storage Unit 2122
Communication Infrastructure 2106
2128
Communications Interface 2124
Communications Path 2126

FIG. 21